

Datasheet 10P1

Articlenumber 1000009

Halfbridge Transducer 73.75 mV/Vmm sensitivity and \pm 0.25 mm measuring stroke. Cable 2 m, cable exit radial. (ex Machsize and Nairda)



Total Stroke, Measuring stroke, Pretravel, Pretravel default setting, Bearing, Lifetime, Tip rotation, Temperatur range, Mounting position, Tip, Bellow, Body diameter, Plug, Cable feature, Cable information

Total Stroke	0.8 mm
Measuring stroke	± 0.25 mm
Pretravel	not adjustable
Pretravel default setting	- 0.35 mm
Bearing	Ball bearing, no side-play
Lifetime	> 10 Mio. Cycles
Tip rotation	1° over full stroke
Temperatur range	-10 to +65 °C, storage and operation
Mounting position	any
Тір	4 mm tungsten carbide ball
Bellow	FPM / FKM
Body diameter	8h6
Plug	5 pin, 240°
Cable feature	PUR shielded, Length 2 m
Cable information	Outer- ϕ 2.0 mm, drag chain compatible

Advance, Spring rate, Spring rate information

Advance	spring push
Spring rate	0.63 N
Spring rate information	at electrical zero, tolerance ± 20%



Innovative Measurement Technology Ltd

www.innovative-measurement-technology.co.uk

sales@imeasure.co.uk +44 (0) 1243 942010



Datasheet 10P1

Articlenumber 1000009



Repeatability, Linearity error		
Repeatability	0.01 µm	
Linearity error	0.8% FS (full-scale) \pm 250 μ m range (at 20 °C \pm 1°C)	
Sensitivity, Amplifier input load, Drive frequency, Supply voltage, Coil scheme		
Sensitivity	73.75 mV/(Vmm)	
Amplifier input load	2 kOhm Input resistance, ± 0.1%	
Drive frequency	13.0 kHz ±5%	
Supply voltage	3.0 V ±0.5%RMS	

Supply voltage	3.0 V ±0.5%RMS
Coil scheme	Halfbridge, TESA® compatible

Documents information	
Documents information	All drawings and 3D models are shown in "electrical zero" position.



Precision through Innovation

@IMTmetrology



Innovative Measurement Technology Ltd

Unit 3E Vinnetrow Business Park Vinnetrow Road, Chichester West Sussex PO20 1QH United Kingdom E-mail: sales@imeasure.co.uk E-mail: support@imeasure.co.uk Tel: +44 (0) 1243 942010

www.innovative-measurement-technology.co.uk

The contents of this literature are as of January 2023. Innovative Measurement Technology reserves the right to change product specifications without prior notice.

