

Datasheet T851

Articlenumber 1002227

Fullbridge Block Gauge with 150.00 mm/Vmm sensitivity and ± 1 mm measuring stroke, Pretravel adjustable. Cable 2 m, cable exit axial.



Total Stroke, Measuring stroke, Pretravel, Pretravel default setting, Bearing, Lifetime, Tip rotation, Temperatur range, Mounting position, Tips, Plug, Cable feature, Cable

Total Stroke	6.0 mm
Measuring stroke	± 1.0 mm
Pretravel	adjustable
Pretravel default setting	- 1.2 mm
Bearing	Ball bearing, no side-play
Lifetime	> 10 Mio. Cycles
Tip rotation	1° over full stroke
Temperatur range	-10 to +65 °C, storage and operation
Mounting position	any
Tips	can be mounted
Plug	5 pin, 240°
Cable feature	PUR shielded, Length 2 m
Cable information	Outer- \emptyset 4.0 mm, drag chain compatible

Advance, Spring rate, Spring rate information, Spring rate optional, Optional pneumatic retraction and feed

Advance	mountable
Spring rate	1.0 N
Spring rate information	at electrical zero, tolerance ± 15%
Spring rate optional	0.4 N / 0.63 N / 1.6 N / 2.0 N / 2.5 N / 4.0 N
Optional pneumatic retraction and feed	Pneumatic cylinder assembly T800/88000





Datasheet T851

Articlenumber 1002227



Repeatability, Linearity error	
Repeatability	$0.01\mu m$
Linearity error	0.25% FS (full-scale) \pm 1000 μ m range (at 20 °C \pm 1°C)

Sensitivity, Setting, Amplifier input load, Supply voltage, Drive frequency, Coil scheme		
Sensitivity	150.00 mV/(Vmm)	
Setting	1:1	
Amplifier input load	100 kOhm Input resistance, ± 0.1%	
Supply voltage	3.0 V ±0.5%RMS	
Drive frequency	5.0 kHz ±5%	
Coil scheme	Fullbridge (LVDT)	

Documents information	
Documents information	All drawings and 3D models are shown in "electrical zero" position.



Precision through Innovation @IMTmetrology



Innovative Measurement Technology Ltd

Unit 3E Vinnetrow Business Park Vinnetrow Road, Chichester West Sussex PO20 1QH United Kingdom E-mail: sales@imeasure.co.uk E-mail: support@imeasure.co.uk Tel: +44 (0) 1243 942010

www. innovative-measurement-technology. co. uk

The contents of this literature are as of January 2023. Innovative Measurement Technology reserves the right to change product specifications without prior notice.



